Penlon Diamond MRI Laryngoscope Range

INTUBATION SOLUTIONS

- Designed specifically for use in the MR environment
- Safe to use in a static magnetic field of 3.0 tesla or less
- Macintosh (American and English),
 Miller, and Wisconsin blade styles
- Standard and short handles available
- High intensity Xenon light bulb
- Long life lithium battery





Penlon Diamond MRI Laryngoscope Range

INTUBATION SOLUTIONS



Use your Penlon Diamond MRI laryngoscope safely in MR conditions with a static magnetic field of 3.0 tesla or less.

The Penlon Diamond MRI Laryngoscope Range has been developed through extensive research into the requirements of both diagnostic and interventional Magnetic Resonance (MR) intubation.

Clinicians can intubate in the MR environment safe in the knowledge that the Diamond MRI Range has been independently tested and certified to be MR-Conditional in a static magnetic field of 3.0 tesla or less, and a highest spatial gradient field of 720 gauss/cm or less.

Xenon lamp

The laryngoscope's high-intensity halogen lamp provides a clear, bright and cool light output via the fibre optic light guide, and is powered by a single, replaceable low-magnetic signature lithium battery (C size).

Lithium battery

This advanced technology MR-conditional battery provides exceptional performance compared to standard-type batteries normally used in intubation instruments, and is rated at 8 hours continuous use.

Blades and handles

The fibre optic laryngoscope blades are available in a range of sizes in American and English Macintosh, Miller and Wisconsin patterns. The laryngoscope handle is available in standard or short configuration.

The extensive range of blade and handle configurations means that clinicians in the MR environment now have easy access to the exact laryngoscope to suit their requirements for the patient profile.

- 1 American Macintosh blades Available in sizes 0, 1, 2, 3, 3,5 and 4
- 2 English Macintosh blades Available in sizes 1, 2, 3 and 4
- 3 Miller blades Available in sizes 0, 1, 2, 3 and 4
- 4 Wisconsin blades Available in sizes 2, 3 and 4

- Independently tested and certified to be MR-Conditional
- Blade and handle combinations for the majority of patient profile groups
- 3.9 volt xenon lamp delivers a high intensity, cool, light beam
- Patented low-magnetic signature lithium battery delivers up to 4 times the useful life of a standard battery







facebook.com/PenlonGlobal



linkedin.com/company/penlon-ltd



twitter.com/PenlonGlobal

Doc. No. DMR0118SL / September 2018. Penlon, InterMed and Prima are trademarks of Penlon Limited. All other trademarks are the property of their respective owners

Part of the InterMed Group

© Penlon Ltd. 2018 All rights reserved

Penlon Limited Abingdon Science Park Barton Lane, Abingdon 0X14 3NB, UK

General

- t +44 (0) 1235 547000
- f +44 (0) 1235 547041
- w www.penlon.com

International Sales

- t +44 (0) 1235 547001
- f +44 (0) 1235 547021
- e international.sales@penlon.com e uk.sales@penlon.com

UK Sales

Technical Support

t +44 (0) 1235 547060

f +44 (0) 1235 547061



